





Ergonomic. Excellent. Effective

Numo is a critical care ventilator that provide positive pressure ventilatory support for patients suffering from respiratory failure. NUMO is sensitive to patient effort. The ergonomically designed NUMO is a reliable, cost-effective ventilator.





360° Intelligent safety alarms

NUMO features a series of prioritised alarms. Both audio and visual alerts are provided.



Touch Display

A 7" LCD Colour display makes parameters clearly readable from a distance. A Resistive Touch display with safety lock to avoid accidental changes to settings



Built-in battery backup

The 2-hour battery backup provides uninterrupted support during extended power failures and during intrahospital transfers.



Low Noise levels

NUMO reduces noise-stress .This is particularly valuable for ICUs.



Lightweight and Sleek design

The electronic blender and battery are built into the device, making transportation effortless.

Ventilation modes

Invasive

 $\ensuremath{\mathsf{PC-AC}}$ ($\ensuremath{\mathsf{Pressure}}$ Controlled Assist Control)

VC-AC (Volume Controlled Assist Control)

 $\label{eq:product} PC\text{-}SIMV \mbox{ (Pressure Controlled-Synchronized intermittent mandatory ventilation)}$

VC-SIMV (Volume Controlled-Synchronized intermittent mandatory ventilation)

PRVC- SIMV (Pressure Regulated Volume Control - Synchronized intermittent mandatory ventilation)

 $\mathsf{CPAP}/\mathsf{PSV}$ (Continuous Positive Airway Pressure with Pressure support)



 $NIV\mathchar`-\mbox{PC}$ (Non Invasive Ventilation - Pressure control)

NIV-PS (Non Invasive Ventilation - Pressure Support)

HFNC Therapy (High Flow Nasal Cannula)



Monitoring Display of up to 16 monitoring parameters



Real-time Waveforms Pressure, Volume, Flow



Event log Storage and display of up to 1,000 events with date and time



Technical Specifications		
PARAMETER	RANGE	UNIT
PIP	1 - 60	cmH ₂ 0
PEEP	0 – 30	cmH₂0
Pressure Support	0-40	cmH ₂ 0
FiO ₂	21- 100	%
Respiratory rate	4 - 60	bpm
Tidal volume	50 - 2000	ml
Flow triggers	1 – 10	lpm
Pressure triggers	1- 10	cmH₂0
Inspiratory time	0.3 – 8	sec
Apnea interval	10 – 60	sec
I:E	1:4 - 4:1	

PERFORMANCE SPECIFICATIONS

PARAMETER	ACCURACY
Inspired Pressure	± (2 + (4% of set pressure)) in cmH20
Fi0 ₂	± 3% from set FiO2 in % both Volume and pressure controlled modes
Inspired Tidal Volume	± (10 + (10% of set volume)) in ml
Expired Tidal Volume	± (10 + (10% of actual volume)) in ml

PROCEDURES

100% O2 for suction procedure (2 minutes) Inspiratory Hold - 10 Sec

Expiratory Hold - 10 sec

Accessories

Standard

- Patient circuits
- ► HME filter
- ► BV filter
- Exhalation Valve
- Flow sensor
- Test lung

Optional

- ► Compressor
- ► Humidifier
- ▶ NIV mask
- ▶ High Flow Nasal Cannula

Phoenix Medical Systems Private Limited